

15WM



- For Drilling Rigs with Chain or Cable PULL DOWN
- Constructed from alloy steel for durability
- For MUD and AIR drilling
- Can be furnished with bail
- Trunnion Pins to 1-3/4"
- Thrust ball bearing for supporting pipe load and radial load
- Designed for easy service and field maintenance
- Choice of Lower Connection Threads

TECHNICAL DATA

PACKING	LENGTH OVERALL	WT/LBS EACH	HOSE CONN. FEMALE	LOWER CONN.	WORKING PRESSURE	FLUID OPENING
FIXED	19 1/2"	80	2" NPT	2 7/8" IF LH	To 300 PSI	2"

SAFE WEIGHT LOADS

STATIC LOAD	ROTATING LOAD	DRILL DEPTH	SIZE/WT/FT
30,000 LBS.	27,000 LBS. @ 100 RPM	2,700 FT	2 3/8" / 6.65 LBS
		1,800 FT	2 7/8" / 10.4 LBS

PARTS LIST

PART NO.	DESCRIPTION	WT/LBS	QTY. REQ.
15WM-3600-XX	WESTERN SWIVEL, LESS BAIL, 2" NPT FEMALE HOSE CONNECTION, FOUR (4) PULLDOWN TRUNNION PINS, WITH 2 7/8" IF LH PIN LOWER CONNECTION		
	ADD FOR BAIL		
	ADD FOR SPECIAL LOWER CONNECTION		
15WM-01	BAIL	25.00	1
15WM-02	+ WEARBUSHING RETAINER	3.00	1
15WM-03	BOLT AND LOCKWASHER, W/B RETAINER	.10	4
15WM-04	GOOSENECK, 2" NPT FEMALE HOSE CONNECTION	24.00	1
15WM-05	+ PACKING	.12	2
15WM-05-90	PACKING, 90 DURO (HIGH PRESSURE)	.12	Option
15WM-05V	PACKING, VITON	.12	Option
15WM-06	+ WEARBUSHING	1.00	1
15WX-07	+ HOUSING SEALS	.25	2
15WX-07V	HOUSING SEALS VITON	.25	Option
15WM-08	BEARING SPINDLE	10.00	1
15WX-09	+ SHIELD SEAL	.20	1
15WX-10	+ BEARING SHIELD	.25	1
15WX-12	+ BEARINGS	5.00	5
15WM-14A	BEARING HOUSING, (4) 1 3/4" OD ON 7" SHOULDERS	24.00	1
15WM-15	STUDS AND NUTS, BEARING HOUSING	.75	4
15WM-16GD-LP	LOWER CONNECTION, 2 7/8" OD 8-V LH PIN	12.00	1
15WM-16GE-LP	LOWER CONNECTION, 2 7/8" IF LH PIN	12.00	1
15WM-16FE-LP	LOWER CONNECTION, 2 3/8" IF LH PIN	12.00	1
15WX-17	+ SPINDLE THREAD SEAL	.06	1
15WM-40	MAINTENANCE KIT (8) 15WM-05 (1) 15WM-06		
15WM-40R	REPAIR KIT + Included in repair kit		

Other sizes of connections available, please consult factory.

Option for above swivel, may affect pricing of complete swivel. Other options available, please consult factory.

